

DFCV-AD EC 9126

Previous generation products

Engineering data

REMARK: Do not use for construction. Refer to factory certified dimensions & weights. This page includes data current at time of publication, which should be reconfirmed at the time of purchase. In the interest of product improvement, specifications, weights and dimensions are subject to change without notice.

General notes

- 1. Adiabatic cooler capacities are tested according to EN 1048 for dry coolers.
- 2. TrilliumSeries Coolers of models with D6xx coil configuration have inlet and outlet connections at opposite ends.
- 3. Adiabatic pre-cooling sections are shipped separately and need to be installed on site.

Last update: 15/04/2024

DFCV-AD EC 9126



1. Fluid inlet connection; 2. Fluid outlet connection; 3. Pre-cooler water drain; 4. Electrical panel; 5. Pre-cooler city water connection; 6.Pre-cooler pad.



Model	Nr. of Fans	Weights (kg)			Dimensions (mm)			Air Flow (m³/s)		Tube	Surface	Connecti
		Oper. Weight (kg)	Ship. Weight(k g)	Heaviest Section (kg)	L	W	н	Δ	Y	Internal Volume (dm³)	(m²)	ons
DFCV EC912 6-D61 3-E- AD	12	4850	3985	3985	7152	2820	2735	69.6	69.6	548.0	5208. 0	4
DFCV EC912 6-D61 6-E- AD	12	5520	4330	4330	7152	2820	2735	72.0	72.0	860.0	4672. 0	4
DFCV EC912 6-M61 3-E- AD	12	4850	3985	3985	7152	2820	2735	69.6	69.6	548.0	5208. 0	4
DFCV EC912 6-M61 6-E- AD	12	5520	4330	4330	7152	2820	2735	72.0	72.0	860.0	4672. 0	4
DFCV EC912 6-S61 3-E- AD	12	4850	3985	3985	7152	2820	2735	69.6	69.6	548.0	5208. 0	4
DFCV EC912 6-S61 6-E- AD	12	5520	4330	4330	7152	2820	2735	72.0	72.0	860.0	4672. 0	4
DFCV EC912 6-T61 3-E- AD	12	4850	3985	3985	7152	2820	2735	69.6	69.6	548.0	5208. 0	4