



# SP 3A EC D613-E - T613-E

Previous generation products

## Engineering data

**REMARK:** Do not use for construction. Refer to factory certified dimensions & weights. This page includes data current at the time of publication, which should be reconfirmed at the time of purchase. In the interest of product improvement, specifications, weights and dimensions are subject to change without notice.

**Last update:** 26/04/2024

SP 3A EC D613-E - T613-E



1. Fluid inlet connections; 2. Fluid outlet connections; 3. Pre-cooler water drain; 4. Electrical panel; 5. Pre-cooler city water connection; 6. Pre-cooler piping drain.  
On model SP 3A EC D613-E the fluid-in connections are located at the opposite side of the unit.

| Model            | Nr. of Fans | Weights (kg)      |                  |                       | Dimensions (mm) |      |      | Air Flow (m³/s) |      | Tube Internal Volume (dm³) | Surface (m²) | Connections |
|------------------|-------------|-------------------|------------------|-----------------------|-----------------|------|------|-----------------|------|----------------------------|--------------|-------------|
|                  |             | Oper. Weight (kg) | Ship. Weight(kg) | Heaviest Section (kg) | L               | W    | H    | Δ               | Y    |                            |              |             |
| SP 3 A-EC-D613-E | 3           | 2290              | 1880             | 1880                  | 4016            | 2206 | 2523 | 21.6            | 21.6 | 254.0                      | 2388.0       | 2           |
| SP 3 A-EC-H613-E | 3           | 2290              | 1880             | 1880                  | 4016            | 2206 | 2523 | 21.6            | 21.6 | 254.0                      | 2388.0       | 2           |
| SP 3 A-EC-L613-E | 3           | 2290              | 1880             | 1880                  | 4016            | 2206 | 2523 | 21.6            | 21.6 | 254.0                      | 2388.0       | 2           |
| SP 3 A-EC-M613-E | 3           | 2290              | 1880             | 1880                  | 4016            | 2206 | 2523 | 21.6            | 21.6 | 254.0                      | 2388.0       | 2           |
| SP 3 A-EC-S613-E | 3           | 2290              | 1880             | 1880                  | 4016            | 2206 | 2523 | 21.6            | 21.6 | 254.0                      | 2388.0       | 2           |
| SP 3 A-EC-T613-E | 3           | 2290              | 1880             | 1880                  | 4016            | 2206 | 2523 | 21.6            | 21.6 | 254.0                      | 2388.0       | 2           |